











Technical data

Voltage	100 — 240 Vac
Output Voltage	24 Vdc; 4.5A
Max. cable section	1.3 mm²
Operating temperature	(- 10) − (+ 55) °C
IP degree of protection	IP30
Maximum relative humidity	93%
Operating frequency	50 – 60 Hz

Warnings and consumer rights



Read carefully before use and keep for future reference

Touching the units with wet hands is forbidden Using liquid cleaners or aerosols is forbidden Blocking the ventilation openings is forbidden Modifying the devices is forbidden Removing protective parts from the devices is forbidden Installing the units near liquids and powders is forbidden Installing the units near heat sources is forbidden Installing the units near harmful gases, metal dusts or similar is forbidden

Fastening the units on unsuitable surfaces is forbidden



Danger of electrical shock



 $Risk of devices falling \ because the surface on which they are installed \ collapses \ or \ in appropriate \ installation$ Switch the power supply OFF before any work on the system

Caution: Installation, configuration, starting-up and maintenance must be performed exclusively by



qualified personnel.
Check that the wall installation has been carried out correctly
Lay out the wires respecting the standards in force
Connect the power supply wires as indicated Use only the items indicated in the technical specifications for any system expansions $% \left(\frac{1}{2}\right) =\frac{1}{2}\left(\frac{1}{2}\right) \left(\frac{1}{2}$